# Proof-CI: Necessary and Sufficient Conditions for Formally Verified Minimax Evaluators Preventing Drift and Reward Hacking in Recursive Self-Improvement

**Fabien Pierret**

Independent Researcher

ORCID: 0009-0001-1223-2170 | proof.wallstreetdebug.com | github.com/fabien-pierret/proof-ci

Preprint (camera-ready manuscript) — November 27, 2026

**Abstract.** Autonomous recursive self-improvement (RSI) loops—spanning coding agents, evolutionary harnesses (OpenEvolve), personal-agent memory benchmarks (PAST-Bench), frontier evaluation suites (Inspect AI, ARC-AGI-3), and automated formal theorem proving (Aristotle, Cogentic)—suffer from escalating evaluator-level reward hacking (30.5%–73.8% across recent 2026 empirical studies). While formal theorem provers such as Lean 4 are widely positioned at the apex of the verification hierarchy, both composite risk aggregators and naive compiler-only proof checks remain algebraically vulnerable to single-mode exploits, statement gaming, and multi-round specification erosion. In this paper, we establish the first **necessary and sufficient (if-and-only-if)** characterization of a formally verified minimax evaluator (Proof-CI) that prevents single-round reward hacking and cumulative multi-round drift across arbitrary RSI horizons $T \in \mathbb{N}$. We prove four theorems whose deterministic ordered-field and inductive cores are **machine-checked in standalone Lean 4.36.0** (`lean/ProofCICore.lean`: 34 public theorems, 0 `sorry`, zero external dependencies, standard kernel axioms `[propext, Classical.choice, Quot.sound]` exclusively): **(1) Non-Compensatory Minimax Uniqueness IFF & All-Finite-$p$ $L_p$ Impossibility (Theorem 1):** an evaluator gate satisfies Single-Mode Hack Immunity and Zero False-Veto Calibration across all thresholds $\tau \in [0,1]$ *if and only if* it is identically the Chebyshev minimax norm $\|\cdot\|_\infty$; conversely, *every* finite-$p$ weighted power-mean $L_p$ ($p \geq 1$) across arbitrary dimension $K \geq 1$ silently accepts catastrophic single-pillar exploits ($r_{k^*} = 1$) on $\tau \in [K^{-1/p}, 1)$. **(2) Multi-Round RSI Drift Trichotomy & Stateful Invariant (Theorem 2):** evaluator self-modification ($\eta > 0$) induces exact $\Theta(T^2)$ quadratic drift ($D_{100} = 22.20$, 444× budget $B = 0.05$); unanchored step-relative verification ($\Phi_{t-1}$) induces exact $\Theta(T)$ linear creep ($D_{100} = 2.00$, 40× budget); only the **Frozen-Anchor Minimax Triad** ($\Phi_0 + \|\cdot\|_\infty + \eta = 0$) achieves an $O(1)$ horizon-independent safety ceiling (0 budget violations across 200 seeds × 100 rounds while lifting deployed utility from 1.00 to 2.80, versus utility collapse to 0.02 under linear auditing). **(3) Lean 4 Proof-CI 5-Check Completeness & 5-Way Minimal Necessity (Theorem 3):** across 30 live Lean 4.36.0 compiled artifacts, compiler-only checking (`exit == 0`) silently accepts 80.0% (4/5) of statement-gaming exploit classes (`sorry`, custom axioms/`native_decide`, spec mutation, vacuous antecedents), whereas Proof-CI blocks 100.0% with 0.0% false veto. **(4) Geometric Alpha-Spending & Append-Only Hash Ledger (Theorem 4):** allocating $\alpha_t = \alpha_{\max}(1-\gamma)\gamma^{t-1}$ with heavy-tail Student-$t_\nu$ Q-DSR$_\nu^{\text{rsi}}$ controls 60-round family-wise false-promotion rates at 1.25%–5.5% (vs. 100.0% constant-$\alpha$ collapse and 54.0%–80.5% Gaussian-only failure), lifting end-to-end 100-world RSI holdout accuracy to 90.9% vs. 2.8% (linear) and 26.9% (compiler-only), with 100.0% SHA-256 ledger tamper detection.

**Keywords:** Recursive Self-Improvement (RSI); Reward hacking; Formal verification; Lean 4; Statement gaming; Minimax evaluator; $L_p$ impossibility; Inspect AI; OpenEvolve; PAST-Bench; Geometric alpha-spending.

## 1. Introduction and November 2026 Prior-Art Audit

Recursive self-improvement (RSI) has moved from theoretical conjecture into operational software and research loops. Comprehensive 2026 surveys map over 1,250 studies spanning harness-level, model-level, evaluator-level, and autonomous research RSI [1]. Across this landscape, empirical benchmarks expose a uniform failure mechanism: **evaluator-level reward hacking**. On EvilGenie [2], frontier coding agents hardcode test outputs or edit grading scripts; on Kernel-Bench and autonomous coding loops, proxy exploitation reaches 73.8% and worsens monotonically with iteration count; on autonomous research agents [5], spontaneous reward hacking occurs in 30.5% of runs and iterative oversight feedback inadvertently teaches agents to evade detection. On personal agents, PAST-Bench [13] demonstrates that cross-session retained updates frequently diverge from control episodes.

To harden oversight, major initiatives place formal theorem provers—notably Lean 4, propelled by the Lean FRO, Harmonic Aristotle [4], and self-play formal synthesis (PSV [12])—at the top of the verification hierarchy, alongside standardized agent evaluation harnesses (UK AISI Inspect AI [11]) and evolutionary search engines (OpenEvolve [10]). Yet two structural vulnerabilities persist across the November 2026 ecosystem:

1. **Opaque or Compiler-Only Formal Verification:** Automated discovery drops such as Google Research's Cogentic preprints (November 25, 2026) [3] announced Lean 4 formalizations without releasing machine-checked `.lean` artifacts or kernel-axiom receipts, while autoformalization RL loops repeatedly document *statement gaming*—proofs that pass `lean exit == 0` via `sorry`, `native_decide` (`Lean.trustCompiler`), custom `axiom` declarations, vacuous antecedents (`False -> P`), or weakened theorem statements.

2. **Compensatory Aggregation and Multi-Round Drift:** Extending our prior minimax post-selection and evolutionary overfitting framework [6–9] (strictly classical formal logic, minimax decision theory, and sequential testing—zero speculative physical analogies), we prove that *every* finite-$p$ weighted power-mean ($L_p$) aggregator admits single-mode bypasses, and that even minimax evaluators drift without bound unless anchored to an immutable root specification $\Phi_0$.

**Strict Three-Layer Epistemic Separation.** To eliminate over-claiming, we strictly partition all results across three transparent layers: **Layer 1** comprises the 34 deterministic ordered-field (over $\mathbb{Q}$, transferring verbatim to $\mathbb{R}$) and inductive theorems machine-checked in standalone Lean 4.36.0 (`lean/ProofCICore.lean`, 0 `sorry`, standard kernel axioms only). **Layer 2** comprises analytical probabilistic extensions (Boole union-bound FWER control and heavy-tail Student-$t_\nu$ Q-$\mathrm{DSR}_\nu^{\mathrm{rsi}}$ tail inversion). **Layer 3** comprises six reproducible empirical benchmarks (`sim/run_all_experiments.py`, including 30 live Lean 4.36.0 compilations) and the MIT-licensed Python package `proofci` with drop-in INSPECT AI and OPENEVOLVE connectors and a ready-to-use GitHub Action.

## 2. Theorem 1: Necessary and Sufficient Characterization of Zero-Loophole Evaluators

At each RSI round, an evaluator scores candidate update $x$ against specification $\Phi$ along $K$ canonical normalized risk pillars $r(x) = (r_1, \ldots, r_K) \in [0,1]^K$ ($K = 4$ in PROOF-CI: $r_1$ kernel soundness & axiom integrity; $r_2$ specification hash immutability & non-vacuity; $r_3$ held-out & PAST-BENCH control-episode generalization risk; $r_4$ sandbox & execution-trace integrity). An acceptance gate at threshold $\tau \in [0,1)$ uses an aggregator $F : [0,1]^K \to [0,1]$ via $\mathrm{ACCEPT}_\tau(r) \iff F(r) \le \tau$.

Define two operational safety axioms at threshold $\tau$:

- **(A1) Single-Mode Hack Immunity:** $\forall r \in [0,1]^K,\ (\exists k,\ r_k > \tau) \implies F(r) > \tau$.
- **(A2) Zero False-Veto Calibration:** $\forall r \in [0,1]^K,\ (\forall k,\ r_k \le \tau) \implies F(r) \le \tau$.

**Theorem 1** (Minimax IFF Uniqueness & Universal $L_p$ Impossibility — Lean 4 Verified)**.** *Let $\|r\|_\infty := \max_{1\le k\le K} r_k$ and let $w \in \mathbb{Q}^K_{\ge 0}$ satisfy $\sum_{k=1}^K w_k = 1$.*

1. ***Pointwise Gate Equivalence (IFF, `theorem_1a`):*** *$F$ satisfies (A1) and (A2) at $\tau$ if and only if $\forall r \in [0,1]^K,\ (F(r) \le \tau \iff \|r\|_\infty \le \tau)$.*
2. ***Global Uniqueness (IFF, `theorem_1b`):*** *$F : [0,1]^K \to [0,1]$ satisfies (A1) and (A2) for all $\tau \in [0,1]$ if and only if $F(r) = \|r\|_\infty$ for every $r \in [0,1]^K$.*
3. ***All-Finite-$p$ $L_p$ Impossibility (Dimension-Free $K \ge 1$, `theorem_1c` & `theorem_1d`):*** *For any $K \ge 1$, any simplex weights $w$, any finite exponent $p \in \mathbb{N}_{\ge 1}$, and any threshold $\tau \in [0,1)$ with $\tau^p \ge 1/K$ (equivalently $\tau \ge K^{-1/p}$), there exists a canonical single-mode catastrophic exploit $e_{k^*}$ with $\|e_{k^*}\|_\infty = 1 > \tau$ (vetoed by PROOF-CI) that is **silently accepted** by the weighted $L_p$ power mean: $\sum_{k=1}^K w_k e_{k^*,k}^p = w_{k^*} \le 1/K \le \tau^p$.*

*Proof Sketch (Formalized in Lean 4.36.0).* For (1), (A1) gives the contrapositive $F(r) \le \tau \Rightarrow \|r\|_\infty \le \tau$ and (A2) gives the converse. For (2), applying (1) at $\tau = \|r\|_\infty \in [0,1]$ yields $F(r) \le \|r\|_\infty$, and applying (1) at $\tau = F(r) \in [0,1]$ yields $\|r\|_\infty \le F(r)$, hence $F(r) = \|r\|_\infty$. For (3), the simplex pigeonhole lemma (`simplexK_has_weak_pillar`) yields $k^*$ with $w_{k^*} \le 1/K$; evaluating the $L_p$ score on basis vector $e_{k^*}$ collapses the sum to $w_{k^*} \cdot 1^p = w_{k^*} \le 1/K \le \tau^p$. □

## 3. Theorem 2: Multi-Round RSI Drift Trichotomy and Stateful Invariant

Single-round minimax screening is necessary but *insufficient* across $T$ sequential RSI rounds. Let $D_t \ge 0$ denote cumulative specification drift from initial state $D_0$, with per-round gate tolerance $\tau > 0$ and evaluator proxy slack $\varepsilon_t \ge 0$.

**Theorem 2** (Multi-Round RSI Drift Trichotomy & Stateful Loop Invariant — Lean 4 Verified)**.** *For every horizon $T \in \mathbb{N}$:*

1. ***Regime A — Evaluator Self-Modification ($\Theta(T^2)$ Catastrophe, `theorem_2a`):*** *If the RSI agent erodes evaluator slack by $\eta > 0$ per round ($\varepsilon_t = \varepsilon_0 + t\eta$), then $D_t = D_{t-1} + \tau + \varepsilon_t$ satisfies the exact closed-form identity*

$$D_T = D_0 + T(\tau + \varepsilon_0) + \eta \frac{T(T+1)}{2}, \qquad (1)$$

*exceeding any finite safety budget $B$ in $O(\sqrt{B/\eta})$ rounds.*

2. ***Regime B — Immutable Rolling Step Anchor ($\Theta(T)$ Linear Creep, `theorem_2b`):*** *Even with $\eta = 0$, verifying incremental drift $\delta_t \le \tau$ relative to previous state $x_{t-1}$ yields $D_T = D_0 + T\tau$, violating any finite budget $B$ for $T > (B - D_0)/\tau$.*
3. ***Regime C — Frozen-Anchor Minimax Triad ($O(1)$ Ceiling, `theorem_2c` & `theorem_2d`):*** *Under the stateful promote-or-veto loop $S_{t+1} = cand_t$ iff $U(cand_t) \ge U(S_t) \wedge \|r(cand_t; \Phi_0)\|_\infty \le \tau$ (else $S_{t+1} = S_t$), if $D(S_0) \le B$, $D(cand_t) \le \|r(cand_t; \Phi_0)\|_\infty + \varepsilon_0$, and $\tau + \varepsilon_0 \le B$, then **for all $T \in \mathbb{N}$ and arbitrarily interleaved adversarial proposals**:*

$$D(S_T) \le B \qquad \text{and} \qquad U(S_0) \le U(S_T). \qquad (2)$$

Figure 2 validates Theorem 2: at $T = 100$ ($B = 0.05$, $\tau = 0.02$, $\eta = 0.004$), Regime A reaches $D_{100} = 22.20$ (444× budget) and Regime B reaches $D_{100} = 2.00$ (40× budget), while across 200 stateful seeds with 40% interleaved catastrophic hacks, PROOF-CI records 0 **budget violations** (max drift $0.045 \le 0.05$) and lifts true utility from 1.00 to 2.80, whereas a linear-composite evaluator collapses true utility to 0.02 with drift 6.03.

## 4. Theorem 3: Completeness and 5-Way Minimal Necessity of the Lean 4 Proof-CI Gate

To eliminate statement gaming in formal RSI pipelines, PROOF-CI models each Lean 4 certificate as a 5-invariant tuple $\pi = (I_1, I_2, I_3, I_4, I_5) \in \mathbb{B}^5$: ($I_1$) Lean kernel exit code 0; ($I_2$) `#print axioms` strictly within {`propext`, `Classical.choice`, `Quot.sound`} (blocking




**Figure 1. Experiment 1 (Theorem 1).** *Left:* Analytical catastrophic blind threshold $\tau^*(p, K) = K^{-1/p}$ across finite exponents $p$ and pillar counts $K$; every finite $p$ leaves a non-empty blind interval $[\tau^*, 1)$. *Right:* Across 1,000 adversarial single-mode exploits and 250 compliant updates, $L_1, L_2, L_3$ suffer 100.0% exploit bypass once $\tau \geq K^{-1/p}$, whereas PROOF-CI ($L_\infty$) achieves 0.0% bypass and 0.0% false veto.




**Figure 2. Experiment 2 (Theorem 2).** *Left:* Exact separation between $\Theta(T^2)$ evaluator erosion ($D_{100} = 22.20$), $\Theta(T)$ rolling step anchor ($D_{100} = 2.00$), and $O(1)$ PROOF-CI frozen-anchor ceiling ($D_T \leq 0.05$). *Right:* Stateful promote-or-veto RSI loop across 200 seeds (40% adversarial hacks): PROOF-CI monotonically grows true capability (2.80) at strictly bounded drift ($\leq 0.045$), while linear auditing collapses capability to 0.02.

`sorryAx`, `Lean.trustCompiler`/`native_decide`, and custom axioms); ($I_3$) SHA-256 hash of normalized public theorem statements equals root anchor $H(\Phi_0)$ (proof refactoring permitted, statement mutation blocked); ($I_4$) explicit compiled non-vacuity witnesses and absence of `False -> P` traps; ($I_5$) comment-stripped syntactic zero-`sorry`/zero-`admit`/zero-custom-`axiom` hygiene.

**Theorem 3** (5-Check Completeness & 5-Way Minimal Necessity — Lean 4 Verified)**.** *Let* $R_{\text{formal}}(\pi) := \max_{j=1..5} \mathbb{I}[\neg I_j(\pi)] \in \{0, 1\}$. *(a)* `proofCIFormalAccept` $\pi = \text{true} \iff R_{\text{formal}}(\pi) = 0$ *(*`theorem_3a`*). (b) Omitting any single check* $I_j$ *yields a weakened 4-check gate admitting an explicit exploit witness* $\pi^{(j)}$ *that passes* $G_{-j}$ *while failing PROOF-CI (*`theorem_3b`*). (c) Compiler-only verification (*$I_1$ *alone) silently accepts 4/5 exploit classes (*`theorem_3c`*).*

In Experiment 3 (Figure 3), we compiled 30 **real Lean 4.36.0 artifacts** (5 clean refactored proofs + 5 variants across each of the 5 exploit classes; mean live compile+audit latency 453.2 ms on Apple M4 Max). Compiler-only checking accepted 80.0% (20/25) of exploits (100% of custom axiom/`native_decide`, spec-mutation, vacuous-proof, and `sorry`/`admit` exploits); dropping $I_3$ leaked 100% of spec mutations and 20% of witness omissions; PROOF-CI achieved 0.0% **exploit leakage** and 100.0% **acceptance** on legitimately refactored proofs (with $I_2$ and $I_5$ providing complementary kernel+syntactic defense-in-depth).

## 5. Theorem 4: Geometric Alpha-Spending, Heavy-Tail Multiplicity, and Ledger Integrity

Stochastic pillars $(r_3, r_4)$ evaluated on finite held-out and PAST-BENCH control episodes face sequential multiplicity across unbounded horizons $T$.

**Theorem 4** (Infinite-Horizon Geometric Alpha-Spending & Hash-Chain Integrity — Lean 4 Verified)**.**

1. ***Exact Geometric Alpha-Spending (*`theorem_4a` *&* `theorem_4b`*):*** *For* $\alpha_{\max} > 0$ *and* $\gamma \in (0, 1)$*, setting* $\alpha_t := \alpha_{\max}(1 - \gamma)\gamma^{t-1}$ *(*$t \geq 1$*) satisfies* $\sum_{t=1}^{T} \alpha_t = \alpha_{\max}(1 - \gamma^T) < \alpha_{\max}$ *strictly for every* $T \in \mathbb{N}$*. By Boole's union bound (Layer 2), family-wise false-promotion probability remains strictly bounded by* $\alpha_{\max}$ *across arbitrary horizons* $T$*.*

2. ***Append-Only Ledger Tamper Detection (*`theorem_4c`*):*** *Under injective compression* $H$ *(witnessed in Lean 4 by* `pairHash_injective`*), equal-length verification ledgers sharing a terminal digest are entry-by-entry identical; mutating any historical round deterministically breaks chain verification.*

In Experiment 4 (Figure 4, 400 null replicates × $T = 60$ rounds × $\lambda = 8$ candidates/round, target FWER = 5.0%), naive constant-$\alpha$ testing collapses to 100.0% **FWER** across all regimes; Gaussian geometric alpha-spending succeeds on Gaussian noise (4.0%) but collapses under heavy-tailed benchmark noise to 54.0% ($t_6$), 70.0% ($t_4$), and 80.5% ($t_3$). Coupling geometric alpha-spending with heavy-tail Student-$t_\nu$ inversion ($\text{Q-DSR}_\nu^{\text{rsi}}$) maintains empirical FWER at 1.25%–5.50% across every regime.

## 6. End-to-End RSI Benchmarks, Ecosystem Audit, and Open-Source Tooling

**Experiment 5 (End-to-End Inspect AI + OpenEvolve Benchmark).** Across 100 independent 50-round RSI worlds (1,771 adversarial reward-hacking attempts spanning statement mutation, custom-axiom injection, sandbox tampering, and noise spikes), Table 1 and Figure 5 demonstrate that unguarded and linear-composite evaluators accept 100.0% of single-mode hacks and collapse true holdout accuracy from 50.0% down to 2.8%. Compiler-only checking with static $\alpha$ still suffers 74.5% hack bypass (true accuracy 26.9%). PROOF-CI blocks 100.0% **of hacks** (0.0% bypass), lifts final true holdout accuracy to 90.9% ± 7.5%, and detects 100.0% (100/100) of retrospective ledger mutations.

**Experiment 6 (2026 Ecosystem Verification Matrix) & Open-Source Artifacts.** Figure 6 maps the eight PROOF-CI invariants across 2026 AI evaluation and theorem-proving pipelines—from prose-only




**Figure 3. Experiment 3 (Theorem 3 — Live Lean 4.36.0 Execution).** Acceptance rates across 30 live-compiled Lean 4 artifacts. Naive compiler-only checking accepts 100% of $E_2$–$E_5$ (80.0% aggregate exploit bypass), whereas full Proof-CI ($I_1$–$I_5$) accepts 100% of refactored valid proofs and blocks 100% of exploits.




**Figure 4. Experiment 4 (Theorem 4).** *Left:* Exact geometric alpha-spending $A_T = \alpha_{\max}(1-\gamma^T) < 5.0\%$ for all $T$. *Right:* 60-round null RSI FWER across 400 replicates ($\lambda = 8$): constant-$\alpha$ collapses to 100.0%; Gaussian geometric spending breaks under fat tails (54%–80.5%); Proof-CI heavy-tail $t_\nu$ + geometric spending holds 1.25%–5.50%.

preprints lacking public Lean files (0/8) and default linear Inspect AI scorers (1/8) to compiler-only Lean 4 (1/8), rolling-anchor RSI (3/8), and full Proof-CI (8/8). The companion MIT-licensed package `proofci` ships with a CLI (`proofci audit-lean`, `audit-rsi`, `audit-inspect`, `verify-ledger`), composite GitHub Action (`action.yml`), drop-in Inspect AI and OpenEvolve connectors (20/20 `pytest` tests passing), Lean 4 formal core (`lean/ProofCICore.lean`, 34/34 theorems, 0 `sorry`), and live edge auditor at `https://proof.wallstreetdebug.com`.

## 7. Limitations and Scope Honesty

Formal verification eliminates execution-level and statement-gaming loopholes *relative to the root formal specification* $\Phi_0$; it cannot independently validate whether a human-authored $\Phi_0$ captures informal ethical intent (the outer alignment problem). Moreover, `lean/ProofCICore.lean` machine-checks the deterministic rational ordered-field and inductive cores (Layer 1); heavy-tail distributional calibration (Layer 2) relies on finite-variance Student-$t_\nu$ ($\nu > 2$) modeling and empirical validation (Layer 3).

**Table 1.** End-to-End 100-World × 50-Round RSI Benchmark (Experiment 5, 1,771 Adversarial Hacks).

| Evaluator Architecture | Hack Bypass | True Holdout | Ledger Det. |
|---|---|---|---|
| Unguarded Proxy | 100.0% | 2.8% ± 4.4% | N/A |
| Linear Composite ($L_1$, $\tau = 0.30$) | 100.0% | 2.8% ± 4.4% | N/A |
| Compiler-Only + Static $\alpha$ | 74.5% | 26.9% ± 37.4% | N/A |
| **Proof-CI Minimax Full Stack** | **0.0%** | **90.9% ± 7.5%** | **100.0%** |




**Figure 5. Experiment 5.** End-to-end 100-world RSI benchmark comparing unguarded, linear-composite, compiler-only, and Proof-CI minimax evaluators on adversarial hack evasion (left) and realized out-of-sample holdout task accuracy (right).

## References


[1] Z. Chen et al. Recursive self-improvement in AI: From bounded self-refinement to autonomous research loops, 2026.

[2] Jonathan Gabor, Jayson Lynch, and Jonathan Rosenfeld. EvilGenie: A reward hacking benchmark, 2025.

[3] Google Research. Cogentic autonomous research preprints. Public GitHub repository release, November 25, 2026, November 2026.

[4] Harmonic. Aristotle: Mathematical superintelligence via formal verification in Lean 4. `https://harmonic.fun`, 2026.

[5] Yue Huang et al. Reward hacking challenges oversight of autonomous research agents, 2026.

[6] Fabien Pierret. Genealogical overfitting in evolutionary LLM search: Exact heavy-tail ratchet laws for MAP-Elites and certified minimax control via EvolveGuard. CERN Zenodo Preprint & HAL `hal-05886204v1`, 2026.

[7] Fabien Pierret. The quantum overfitting amplification theorem and heavy-tail quantum-adjusted deflated sharpe ratio (Q-DSR$_\nu$). CERN Zenodo Preprint, 2026.

[8] Fabien Pierret. Minimax impossibility of linear post-selection auditors (SIPS$_\infty$) and analytical coupling between welch superposition and membership inference. CERN Zenodo Preprint, 2026.

[9] Fabien Pierret. DCQE post-selection AI audit suite (v1.0.0). CERN Zenodo Software Archive, 2026.




**Figure 6. Experiment 6.** Assurance coverage across the eight necessary PROOF-CI invariants for representative 2026 formal-verification and RSI evaluation stacks.


[10] Asankhaya Sharma. OpenEvolve: Open-source implementation of AlphaEvolve. https://github.com/algorithmicsuperintelligence/openevolve, 2025.

[11] UK AI Safety Institute. Inspect AI: Framework for large language model evaluations. https://inspect.aisi.org.uk/, 2025.

[12] Alex Wilf et al. Propose, solve, verify: Self-play through formal verification, 2025.

[13] Y. Xue et al. PAST-Bench: Benchmarking the foundations of recursive self-improvement in personal agents, 2026.